# <u>eparco</u>°

# ALLROAD 07528TgCol



D.P.I. CAT.2: EN ISO 20345:2022

TAGLIE: 38/48 (5/13)

MONDOPOINT: 11

MADE IN: P.R.C

### IMMAGINI

# BAKU ESD S3S SR FO HRO

07528tgNRVF



STIRIA ESD S3S SR FO HRO

07528tgNRNR



SOCHI ESD S3S SR FO HRO

07529tgBMGF



# **DESCRIZIONE**

Scarpe antinfortunistiche conformi alla nuova norma EN ISO 20345:2022, realizzate in microfibra idrorepellente e collarino in nylon. Intersuola in Phylon con battistrada in gomma HRO FO CrossGrip.

Leggere, sportive e resistenti, sono adatte sia per l'esterno che per l'interno.

## **CARATTERISTICHE**

#### TOMAIA:

microfibra e nylon idrorepellenti, con rinforzi su punta e tallone.

#### FODERA:

tessuto 3D microforato traspirante.

#### SOLETTA REMOVIBILE:

antistatica in PU a bassa densità con termoformatura ergonomica.

#### SOLETTA ANTIPERFORAZIONE:

in fibra tessile ultraleggera a perforazione zero (PS - chiodo Ø 3,0 mm).

#### PUNTALE:

in composito amagnetico, isolante, resistente a 200J.

#### SUOLA:

phylon + gomma nitrilica HRO FO con assorbimento di energia sul tallone.

#### PLUS

Leggere e resistenti, Metal free.

# **DETTAGLI**

### SUOLA

# **SOLETTA REMOVIBILE**



**LOGHI** e **DECORAZIONI** realizzato in serigrafia



RINFORZI ANTIABRASIONE in microfibra su punta e tallone.



Suola superleggera con intersuola in phylon e battistrada in gomma nitrilica CROSSGRIP FO HRO, con tasselli che garantiscono un elevato grip anche su fondi particolarmente accidentati



**SOLETTA REMOVIBILE** antistatica in PU a bassa densità con termoformatura ergonomica



# ALLROAD 07528TgCol



D.P.I. CAT.2: EN ISO 20345:2022

TAGLIE: 38/48 (5/13)

MONDOPOINT: 11

MADE IN: P.R.C

## **NOTA INFORMATIVA**



	Wildylane (10) - Auly mail: recomparation mark com malation (10) 2014 (10) (recomparation comfort solidity
ind some se	
	gulation (IU) 2014/IUS innovaeurona, combat, validity US and in a certified by one of the following notified boolie
4 Body No. 20 4 0070) - 6 no	n (1887): Via Aquandismo Billo: 27029 Vigoruma (PV): Radj 21): Via Carlos Bilgini 216 - 20063 Comunes nel Naciglio «Nacumano Frankel: 48067 (per ambre 17 - France naturish nelsish am sundam his bar nitrami sentam, al 186
_	Additional resolvements
	Additional requirements
1	SE - Closed brof.orm - Architelis properly - Energy description of satiraryion
-	Un Upper soder personalism and absorption
1	$\square$ - perforation resistance assuming to the type closes solution
	SE - Closed beef area - Architeks property - Energy description of sectoragion
	List perfection resistance according to the type closine minute.
	II contemporari de abale batane
	El 1 mater existence of the whole bodyname
_	er all polyments features
(in animly o	durine) feature
ywhich male et sampletely	the inflated by the source studing use. It is designed to be a present in jury if we wouldn't source which recently the ter-
ton bline	
	Cless In E  I  I  I  I  I  I  I  I  I  I  I  I  I

idditional protection may be provided, and is identified on the product by it marking as fo	
	fran
	Multigrade
. h	
perforation resistance (min. 11001N) metal insant od of Simon Control Natl	,
perforation revisionus (min.) 100% num metal insert al-15 from Control Nad	κ.
perfection ministere (min 1100% & each single rates of 600%) non-motel insert : do 5.0mm Central Med	n n
- Bellel	
Perially Conductive (maximum volutions (100 lbC)	c
Antiniatio (resistance rrange of 100 kG to 1000 MC)	Α
• Intimobilish	
Nationalation of sile samples	14
Californialistics of valor complex	0
Energy absorption of seatingsion (38 locales)	-
Note resistance	WE.
Metalanul protestion	-
Addressionies	65
Committeet	a
South Consultancium	
State of the state	
Note constraint and sales describes	100
. 64	
Sentiagrap to but contact	100
Sentance to Salisal	
Lebbraria	10
As it is impacted to the final term solved the case count has calculate for the grandess of the county of the coun	he seller and the purchaser to amuse, where





## NOTA INFORMATIVA MULTILINGUA: (IT, EN, ES, DE, FR)

Dimensioni: 120 x 165 mm

#### **ETICHETTE**



ETICHETTA TEAMWORK stampata su linguetta (15x60 mm). ETICHETTA ESD stampata sui passalacci. OCCHIELLI rinforzati



ETICHETTA COMPOSIZIONE applicata alla scarpa destra Dimensioni 28 x 28 mm







ETICHETTA "CE". stampata all'interno della linguetta Dimensioni 50 x 15 mm

EURO UK
44 9½

ETICHETTA TAGLIA cucito tra tomaia e linguetta Dimensioni 17 x 14 mm

# **PACKAGING**





SCATOLA PER SCARPE SPARCO TEAMWORK in cartone.
Carta velina interna protettiva.
Dimensioni: 343x258x123mm



ETICHETTA SCARPE su SCATOLA riportante caratteristiche del prodotto, certificazione, numero di lotto, codice, codice QR e codice a barre.

Dimensioni 105x60mm